



ACE MOUNTINGS CO., INC.

11 CROSS AVENUE
SOUTH AMBOY, N.J. 08879
PHONE (732) 721-6200
FAX (732) 721-5005

2" and 3" Deflection Spring Isolators for Caterpillar Standby Diesel Generator Sets

Genset Model	Rating KW	Oper. Wt. lbs.	Q'ty of Support	Hole Sizes inches	High Deflection	
					2"	3"
C9	250, 300	5300	6	.69 x 1.25	811-2H	811-3J
C15	350, 400	8400	6	.69 x 1.25	811-2J	812-3G
C15	350, 400	8400	4	.69 x 1.25	812-2H	812-3H
C18	500, 600	8610	6	.69 x 1.25	811-2K	812-3G
C27	700	14000	6	.71	812-2J	812-3H
3412C	750	15500	6	.71	812-2J	812-3K
C32	1000	18600	6	.87	812-2K	812-3K
C32	1000	18600	8	.87	812-2J	812-3H
3512	1250 (HV)	33000	10	.94 x 1.93	812-2K	814-3J
3512	1250	27800	10	.94 x 1.93	812-2J	814-3G
3512C	1500 (HV)	37000	10	.94, .94x1.93	814-2H	814-3J
3512B	1500	32000	10	.94 x 1.94	812-2K	814-3G
3516B	1750	37000		.81, .94x1.93		814-3G
3516B	2000	37800	12	.81, .94x1.93	812-2K	814-3G
3516B	2250	40000		.96, .94x1.93		814-3J
3516C	2500	42000		.96, .94x1.93		
3516B	1750 (HV)	42000		.96, .94x1.93		
3516C	2000 (HV)	46800	12	.94, .94x1.93	814-2H	814-3J
3516B	2250 (HV)	43600		.81, .94x1.93		
3516C	2500 (HV)	46800		.94, .94x1.93		

Note:

1. High deflection spring isolators are recommended for upper floor, roof top and high efficiency installations.
2. Standard high deflection spring isolators are qualified for UBC zone 2 or IBC Ss ≤ 45%
Contact factory for higher seismic load applications
3. For **global package generator sets**, please contact Ace for proper isolator selection